



Contents lists available at ScienceDirect

## Materials Today: Proceedings

journal homepage: [www.elsevier.com/locate/matpr](http://www.elsevier.com/locate/matpr)

# A critical literature review on minimization of material wastes in construction projects

R. Janani <sup>\*</sup>, N. Lalithambigai

Department of Civil Engineering, School of Engineering, Vels Institute of Science, Technology & Advanced Studies, Tamilnadu, India

## ARTICLE INFO

### Article history:

Received 15 July 2020

Accepted 1 September 2020

Available online xxxx

### Keywords:

Waste materials

Minimization

Construction projects

Materials

Material waste

Task

Impact and environment

## ABSTRACT

Advancement of waste materials has a noteworthy effect at nature. Development of waste materials has a significant impact at the environment. With the requests in forcing essential foundation extends in India, altogether with numerous business and lodging programs, there are huge amount of creation is produced from the development mechanical and industrial zone Hence, the waste generated from the sites must be well dumped. For this, the waste minimization plans is the better way to reduce the waste getting from the sites. Wastage in creation tasks results super monetary and managerial setbacks to owners and contractors.

Not simplest the wastage creates these problems; it also adversely impacts the surroundings very badly. These wastes have to be managed in addition to their influences desires to be nicely studied, as a result we are able to manage the waste technology and powerful utilization may be stepped forward. Whatever the affects over the surroundings and fitness in many cities of India the generation of wastes from the industry is controlled in a terrible manner say no proper planning and management. In this studies planning, discussing the method for the control and effective utilization of waste construction materials can be discussed.

© 2020 Elsevier Ltd. All rights reserved.

Selection and peer-review under responsibility of the scientific committee of the International Conference on Newer Trends and Innovation in Mechanical Engineering: Materials Science.

## 1. Introduction

### 1.1. General

This analysis is predicated on site waste control in building creation through the various methodologies and the motives and assets may be pointed out nicely to lessen the waste. In production of tasks, 4-M (Material, Manpower, Money and Machine) play a prime role and it becomes the main supply of all. Through these wastes, wastage making plans and operation can be implemented so that we can run the sites without problems and can capable of set the overall mission cost through minimization or we will use the materials in right manner. We came to realize that the large amount of waste is generated only from construction enterprises. Though it's difficult to constantly live all the ones wastes in stage by stage activities, partial research from numerous locations have

confirmed that waste represents a comparatively has large proportion.

A large vary of measures are used for looking waste, like excess consumption of substances. Capable administration of waste is a significant part of effects building. Construction waste can be one of the predominant influences to the environment if proper disposal exercise is not adhered. The waste that are generated within the site which occurred at every step of the construction activities should be taken in critical difficulty due to the fact it's affecting the environment very badly. It may be very vital for the responsible disposal of waste to a income development and for a sustainable future. For the waste minimization, the materials wasted that ought to be recycled, reused. The outcomes of the Programme have been in comparison against a similar assignment constructed simultaneously. The outcomes of the trial revealed giant monetary financial savings.

### 1.2. Significance of waste minimization

Waste minimization is a set of procedures and practices supposed to lessen the quantity of waste produced. By lowering or

\* Corresponding author.

E-mail addresses: [Janani.se@velsuniv.ac.in](mailto:Janani.se@velsuniv.ac.in) (R. Janani), [lalitha.vels2018@gmail.com](mailto:lalitha.vels2018@gmail.com) (N. Lalithambigai).

<https://doi.org/10.1016/j.matpr.2020.09.011>

2214-7853/© 2020 Elsevier Ltd. All rights reserved.

Selection and peer-review under responsibility of the scientific committee of the International Conference on Newer Trends and Innovation in Mechanical Engineering: Materials Science.

doing away with the era of harmful and chronic wastes, waste minimization supports efforts to sell a extra sustainable society. Waste minimization entails remodeling merchandise and tactics and/or converting societal styles of consumption and production. The maximum environmentally imaginative, economically green, and value effective way.

An overall extent of 15% much less waste turned into generated on website previous to recycling and 43% much less waste went to landfill. Cost financial savings of 50% had been made in terms of waste managing prices. The financial savings resulted nearly completely from web site primarily based techniques for handling waste.

A complete volume of 15% less waste was produced nearby preceding reusing and 43% less waste went to landfill. Cost reserve funds of half were made as far as waste taking care of charges. The reserve funds came about on the whole from site based systems for taking care of waste.

There are 4 kinds of buildings venture from associate a class's business enterprise that is

- High constructing task
- Industrial constructing challenge
- Commercialize building venture
- Housing constructing assignment

Owing to the quantity of employee inside the construction undertaking is massive, guy of science use the smooth sampling to slender down the sample. Easy sampling guarantees that every unit within the population has an equivalent likelihood to be selected as pattern. Respondent during this evaluation is that the employee of the development task from a awesome creation site.

### 1.3. Scope of the research

The scope of the undertaking is as follows:

The important evaluation is to check the effect. The significant assessment is to check the impact on limit, reuse and diminish system on building appearance manager. On paper, it assumes to offer an influence toward the assembling building undertaking; anyway will it very give an influence nearer to the waste manufacture. During this appraisal explore we have following basic goals are drill down agreement to the depend declaration that has been recognized.

- i. To go over essential utilized limitation, reuse, reuse and reclamation technique at creation
- ii. To discover the association between decrease; reuse, reuse and recuperation procedure and accordingly the waste assembling in creation errands.
- iii. To find the varieties among lower, reuse, reuse and rebuilding method

### 1.4. Objective of research

The objectives of the accepting a glance at are as per the following:

- i. In the principal point, studies can be cultivated on reduce, reuse, reuse and recovery method utilized in the waste control framework on-site online to catch the most extreme utilized 4R systems
- ii. Second objective can see whether or no more or not lower, reuse, reuse and recovery technique utilized offers a basic effect at the aggregate waste assembling. During this reason,

the finding can affirm whether or now not the system utilized on site will decrease or assembling more prominent waste on site on the web.

- iii. The third one is to spot adaptations among decline, reuse, reuse and recovery method utilized, will confirm that of the strategies are minimal effort or no longer underway a dreadful parcel considerably less waste.

## 2. Literature review

### 2.1. Observation from the literature review

Olubenga O. Akinade et al. [1] stated that Development and destruction waste minimization can can be minimized only with the help of softwares BIM. He also conducted the Qualitative focus goup interview with the professionals who are well versed with the BIM technology and thus CDW can be minimized based on those. From the responses, the next step was implemented with ranking and then with the reliability analysis, top factor consideration and then finally with the dimensions of factors with the group formation say (PCA) principal component analysis. Concluded that it is used in UK and hence CD waste minimization can be minimized accordingly and in other countries it should be encouraged for the minimization of waste generated.

Monika mhaske [2] found that construction industries waste generated creates negative impact over the environment very rapidly every year. The damages are caused only due to the repeated factors like design of structures, handling of materials, procurement stage, and management at the site. This paper reveals the 3R, waste management plan, BIM techniques to use for minimization. Here the data's are collected for the activities involved in the site and also rankings are made with the help of survey basis. Finally concluded that RCC, plastering, brickwork are majorly generated waste during stages of activities of work done. This inadequate planning is main cause for waste and it creates effect over the project profit/over run. Systematic analysis is followed and should be encouraged.

Saheed O. Ajayi [3] explained that the construction industry consumes the largest portion of materials from nature and also it creates the landfill waste enormously. This paper involves the Qualitative and Quantitative methods to minimize the waste generated at the site. Field studies were carried out in six sites, thus questionnaire survey is distributed among the people working in construction industry. From the survey, data's are ranked and thus commences site management measures should be encouraged and implemented in every site for reducing the waste generated. Site managers in each site should take responsibility for minimization of material waste and thus discussions and suggestions should be implemented in prior.

S.m. Elgizawy et al. [4] attempted to give a coordinated answer for creating nations that joins endeavors in ghetto advancement and zero waste administration to get a higher effect on the neighborhood the national level, upgrading the waste administration component and lessening the squanders sent to landfills henceforth moving towards the acknowledgment of the zero burn through ideas and simultaneously encouraging the sentiment of character of the inhabitants and taking care of the landownership issue. Also, inferred that improvement through zero waste ideas is a complete answer for the present advancement issue and waste collection issue and ought to be energized by the legislature

Anwar hussain [5] explained that the construction industry mainly depends on the material only. The building materials are essential component in the construction industry. First the waste generated sources should be checked and ranked first. Then the material wise wastage accumulated per year are calculated. This

paper reveals wastes are due to the various factors like poor management, improper handling, improper planning, designs, specifications, standards, resources, lack of knowledge. Thus 3R, Waste Management Plan, BIM, management software helps to track material inflow and outflow and thus waste generated can be reduced accordingly.

Dr.zeyad s.m.khaled [6] said Construction waste management is must for all construction industry to avoid waste generation. In this paper, Construction waste management system is implemented in Iraq(Karbala) through surveying. Under warning thresholds the employees are requested to answer for questionnaire. Then the developed system MS project is used and is tracked throughout the project life time. Results from the survey gives waste percentages of materials at Karbala. Hence computerized construction waste management system is advised to develop for minimal of waste. From the waste percentages of materials, sources can be easily determined. In this per 33% are due to unemployment of waste reduction measures by architects during design stage, and hence concluded that MS project software system provides inflow and outflow and also warning thresholds of waste materials generated.

Jijiyuan wang [7] establishes that waste minimization configuration is the key procedure for waste minimization in industry. Thus to reduce wastes, pre-materialsated components can be encouraged. In this paper venism software is used along with the questionnaire and the loop diagrams are implemented. From the survey of 6–34 storey buildings, data's are collected and significant variables, loops are formed. Considering the rankings prematerial-sated parts, structure change, waste lessening theory factors are picked randomly. Using prematerial-sated components it is achieved that waste reduces upto 84.7% and from waste reduction investment and design modification the waste reduction percentages can be obtained. Thus concluded that loop diagram, questionnaire, stock flow model serves a major role to reduce waste over the life time of project.

M. Osmani [8] clearly said that minimization of construction waste occurs at all the stages of a project life cycle and hence responsibilities should be taken by stake holders, clients, designers and contractors. Here this paper dealt with minimization should be achieved during designing stage itself than implementing the softwares or any other measures in the project running stage. Origins and sources of wastes are determined and concluded as, at the design stage itself the minimization can be achieved rather than at the implementing stage.

Suresh kumar lachimpadi [9] found out that 80% of construction used materials are being used in the industrial sites as it is the major source in project life cycle. Hence the quantities of raw materials used are also responsible for waste generation, the inflow and outflow must be tracked to reduce the waste. BOQ of eight construction sites with medium cost high rised building in Malaysia was selected and environmental management system are implemented over 3 year period.

Tulay esin [10] said, Construction wastes that are dumped into our natural sources which creates bad effect over environment. Here in this paper, survey is done with fifteen questions It incorporates with the three segments, for example, sort of living arrangements, change works done in the habitations lastly about the kind of materials utilized, sum and furthermore about with the old material use. The information's are assessed by utilizing Microsoft Excel and the outcomes can be found in the comparing figures and tables. From this, particularly in living arrangements of Turkey, frequent alterations are foundations for development waste. To forestall the age of development squander, it is prudent to reuse building materials and segments.

### 3. Materials and sources

#### 3.1. Introduction

A creation organization typically esteemed a task with the guide of its profit and misfortune. So as to verify that the contractual workers get the most extreme salary out of the errand, it's far hard to verify that the method utilized will succeed. Along these lines this estimation rate will fill in as a direction to assist the administration with enhancing the methodology of adapting to material, reduce the waste expense and upgrade productiveness. Hypothetically, exhibitions of waste administration underway site are depending on the amount surveyor decision on site. They will report the entirety of the fabric utilized on-site on the web and the entirety of the material dispatched to site on the web. It is urgent for the sum surveyor to assess materials squander for all the fabric that has been purchase, however a great deal of them only here and there use past mission measurements to gauge the level of materials utilized. The expense that for the most part utilized is 2.5%, 5%, 7.5%, 10% and 12.5%.

Any lack of materials is normally proven in percentage form with out studying the factors that contributing in the direction of the ones probabilities. It is significant for the amount surveyor to assess the variables stressed, the materials utilized and kind of crucial predetermination reference so squander charge might be decrease and make increasingly feasible development. The utilized of waste expense estimation from various zone are not, at this point handy and substantially less right because of differentiation scope of work and the dynamic of the part.

#### 3.2. Source of construction waste

Based on past evaluation, the supply of waste will exist all through the development task, whether or not or now not inside the initial degree, fashion stage, creation level until the Operation. The deliver of waste is divided into 5 instructions which might be:





Fig. 3.1. Concept of 4R.

- Procurement degree
- Material management
- Operation stage
- Excessive material

### 3.3. Methodology



This examine goes to be conducted following planned set up that provides route to hunt down the answer of the have a look at queries. All required data and know-how can be obtained through a properly-prepared set up or methodology that outlines numerous degrees in assembling information and expertise.

- The Stage via degree waste calculation of substances is calculated from the Site and through Reconciliation announcement.
- Then, Questionnaire Survey is performed over the working specialists and also with the labours
- Consolidation of facts from engineers/labours comments with the rankings
- Suggestions & Recommendations for the powerful waste control
- Manual and Waste management plan is finally to be organized.

### 3.4. Material management

Material waste also can appear once the material don't seem to be been dealt with well. Material handlings are usually treated vic-

timization mechanical instrumentality Associate in nursing usually with the aid of an unskilled worker. Typically the material is repaired if the harm is tokenize, but a quantity of the materials are irreparable as soon as damage. Several of its cause all through construction phase anywhere time is crucial and work were given to be achieved short. This is frequently as soon as the same old management is difficult to watch. However the maximum motive of waste turn out is reason from vulnerable control and observation, angle and no good enough incentive. Material control and control becomes a variety of difficult in larger comes. Contractors were given to manipulate the element and material that are wished on site.

### 3.5. Material storage

Storage are every now and then now not nicely put together and risky and commonly the materials are hold on in many absolutely exceptional places. Material that expose to moist circumstance and mistaken locations while machineries and car constantly skip can damage the substances can purpose to become worse and subsequently are going to be injury. This may additionally increase the proportion of loss and waste as an end result of the harm material.

Throughout garage, material should be maintain on in accurate technique as an instance and have to be maintain on better than soil degree and protected from the intense atmosphere to thwart the materials from break and mischief. Waste and absence of substances gave because of mixed up material control and the board. Material administration and control turns into an assortment of hard in bigger comes.

### 3.6. Concept of 4R

The "4R" thought which alludes to diminish, reuse, reuse and supplant, especially with regards to creation and utilization, is notable nowadays. It is something like utilizing recyclable substances in more noteworthy than genuine work on, reusing of crude substances if practical and bringing down utilization of assets and quality. These might be done to the entire lifecycles of administrations and items - beginning from format and extraction of crude materials to conveyance, produce, use, disassembling and removal. "4R" can be communicated

## 4. Results and discussions

1. Identifying the top five sports of waste substances generated from unique websites and finding the reasons of waste era and recommendations are encouraged a good way to reduce waste.
2. Avoid inadequate making plans of the construction waste.
3. Trends on the prematerialsated systems or additives can be endorsed as it's far a treatment for the reduction of waste material segregation.
4. Having one character liable for requesting materials should dodge surplus being purchased.
5. Buying sand and gravel in bulk quantity in preference to the free materials enables to lessen wastage
6. Using long lasting substances will postpone the want to replace it, consequently preventing the era of waste.
7. As considering the technical issue, eight factors are identified which can be loss of supervision, terrible storage facilities, errors in layout, layout modifications, human errors, lack of communication skills, lack of waste management thoughts and useless approach of work.

8. Bar code technique is used to facilitate powerful control of construction substances to reduce waste.
9. Avoid insufficient planning of the construction waste.
10. Trends on the prematerialsated structures or components may be advocated as it's miles a remedy for the reduction of waste material segregation.
11. Having one character liable for ordering materials have to keep away from surplus being purchased.
12. Buying sand and gravel in bulk quantity in preference to the free materials helps to reduce wastage
13. Using a long lasting material will put off the want to update it, consequently stopping the era of waste.
14. As considering the technical thing, 8 factors are identified that are loss of supervision, poor storage centers, error in layout, layout adjustments, human blunders, loss of communication, unique skills, loss of waste management ideas and useless technique of work.
15. Bar code system is utilized to encourage compelling administration of creation substances
16. A dependent questionnaire survey with the engineers, contractors, labours need to be carried out for the idea of where waste materials are generated.
17. If relevant , deploying a mini crusher and screener for left over bricks and blocks
18. Arranging a crew for monitor and to manage materials properly with a view to decrease the wastage generated in the site.
19. Site waste control plan should be developed initially i.e. on the time of design level itself so that it will control the wastage generated within the begin of the undertaking.
20. Specific goal have to be fixed for waste reduction further to the objectives of waste restoration and recycled content in the task short.
21. Reports can be generated on waste reduction movements at assessment meetings
22. Selection of durable additives with low waste over their life time should be recommended.
23. Ensure that the overall performance requirements and necessities for waste dimension and reports blanketed in BOQ s, tender files and contracts
24. Development of forecast for waste can be recommended
25. Towards the challenge finishing touch 2 to three weeks in earlier set up a complete website waste audit to understand how waste types and quantities may exchange at some stage in very last completing clean up.
26. Tracking progress and selling waste control plan on the website online meetings can help workers and others to attain the aim in order to reduce the waste Fig. 3.1.

## 5. Conclusion

Based on the critical literature review several points can be concluded and as follows: Since 70.8% of professionals were found to be not very familiar with term sustainable construction, the following recommendations are e made against this backdrop

1. Educational organizations ought to remember the instructing of manageable development for the educational plan of experts in development industry. Meetings and workshops ought to be sorted out to instruct rehearsing experts.
2. Government ought to carefully screen the taking care of and removal of development squander
3. Incentive scheme should be setup by government to rewards firms how embraced construction waste management.
4. Local contracting companies do not seem to be concerned about material waste.

5. High variation in wastage is found for different construction materials at the same project itself.
6. Proper Storage facilities should be encouraged.
7. There is a considerable variance between waste percentages of the same material from site to site
8. A serious absence of the appropriate knowledge of construction materials waste management is found.
9. Most of the generated waste can be avoided by implementing few preventive measures.
10. To reduce waste, the following initiatives are to be taken.
11. Proper material handling
12. The venture exercises are to be arranged at each stage and should have development personals associated with limiting the general wastage
13. Company policies should be framed/ certification from the government to waste minimization on site.
14. Two main stages of building project were identified to have maximum generation of waste (design and documentation stage and construction stage or execution).
15. Segregation of waste at site
16. We recommend that clients, contractor, architect be careful while quoting tender, there should be tender/ contract requirement for good practices waste minimization and management.

## Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

## References

- [1] O. Olubenga, L.O. Akinade, S.O. Oyedele, M.B. Ajayi, H.A. Alaka, H.A. Owolabi, O. O. Arawomo, Designing out construction waste using BIM technology: stakeholders' expectations for industry development, *J. Cleaner Prod.* 180 (2018) 375–385.
- [2] M. Mhaske, construction waste minimization, *Int. Res. J. Eng. Technol. (IRJET)* (2017).
- [3] S.O. Ajayi, L.O. Oyedele, M. Bilal, O.O. Akinade, H.A. Alaka, H.A. Owolabi, Critical management practices influencing on-site waste minimization in construction projects, *Waste Manage.* 59 (2017) 330–339.
- [4] S.m. Elgizawy, S.m. El-haggar, K. Nassar, Slum development using zero waste concepts: construction waste case study international conference on sustainable design, engineering and construction *J. Cleaner Prod.* 180 (2016) 1306–1313.
- [5] Anwar Hussain, Waste management of building materials for sustainable development, *Am. J. Eng. Res. (AJER)* (2015).
- [6] Dr.zeyad s.m.khaled, Dr. Basil S. Alshathr, ali HASan HAdi, "Development of construction material waste management syatem", *Eng & Tech journal vol.33 part (A) no.7*, 2013.
- [7] Jijiyuan Wang, Zhengdao Li, Vivian W.Y. Tam, Identifying best design strategies for construction waste minimization, *J. Cleaner Prod.* (2015) 1–11.
- [8] M. Osmani, Construction waste minimization in the UK: Current pressures for change and approaches, *Procedia – Soc. Behav. Sci.* 40 (2012) 37–40.
- [9] Suresh Kumar Lachimpadi, Joy Jacqueline Pereira, Mohd Raihan Taha, Mazlin Mokhtar, Construction waste minimisation comparing conventional and precast construction (Mixed System and IBS) methods in high-rise buildings: A Malaysia case study, *Resour. Conserv. Recycl.* 68 (2012) 96–103.
- [10] Tulay Esin, Nilay Cosgun, A study conducted to reduce construction waste generation in Turkey, *Build. Environ.* 42 (4) (2007) 1667–1674.

## Further Reading

- [1] P.R. Kalyana Chakravarthy, T. Ilango, S. Chezhiyan, A detailed study on the mechanical and durability properties of hybrid fibre reinforced concrete, *Mater. Today Proc.* 21 (2020) 684–689.
- [2] K.V. Sabarish, P. Paul, J. Jones, An experimental investigation on properties of sisal fiber used in the concrete, *Mater. Today Proc.* 22 (2020) 439–443.
- [3] P.R. Kalyana Chakravarthy, R. Rathan Raj, Analysis on compressive strength of concrete with partial replacement of cement with alccofine, *ARPN J. Eng. Appl. Sci.* 12 (8) (2017) 2392–2395.
- [4] R. Janani, P.R. Kalyana Chakravarthy, T. Ilango, Budget houses for low-income people, *Int. J. Mech. Eng. Technol. (IJMET)* 9 (13) (2018) 109–117.