



Investigation of mechanical properties of friction stir welding aluminium alloy AA7475-T651 and AA2219-O

Raja R ^a, Parthiban A ^a  , Jeyakumar S ^b, Radha Krishnan B ^c

Show more 

 Share  Cite

<https://doi.org/10.1016/j.matpr.2021.10.439> 

[Get rights and content](#) 

Abstract

In this study, two dissimilar aluminium alloys are joined together through friction stir welding, and their microstructure and mechanical properties like hardness and fracture analysis. In this paper, Al alloy AA7475-T651 and AA2219-O is chosen for Friction stir Welding due to the different hardness level. The welding process is executed with the optimized input parameters and the welding joints quality was inspected. Hardness properties were tested in Thermomechanically affected zone, heat-affected zone, and Welding Zone. The fracture analysis method is used to identify the defects in the welding zone. Finally, the quality of the welding is justified by the hardness and fracture analysis, based on the results the welding process can be applied for different harness Al alloys.

Introduction

Friction Stir Welding is derived as the solid-state connecting technique that combines

two facing surfaces with a third body tool. The heat between the tool and the material is produced, leading to an extremely soft area near the FSW tool. It is employed largely on non-heat-treatable alloys, aluminum, and constructions that require a better welding strength without the use of post-solder thermal therapy [1], [2].

Two separate pieces of metal are supported, and the tool is supported (through probe). The progress of the instrument via the joint also indicates the welding area and the tool shaft area. A non-consuming cylindrical shouldering tool is rotated constantly, and fluid in a button joint between the two clamped parts of butted matter at a constant pace with a profiled sonde. The sample is somewhat lower than the weld depth required by the tool shoulder drive at the top of the working area [3], [4].

AA2219-T87 and Al-Mg alloy AA5083-H321 were welded with optimum input parameters such as tool rotational and transverse speed and pin diameter.

Microstructural studies for identifying the quality through investigating the welding zone. Between wear-resistant solving elements and working parts, frictional heat is produced [6]. This thermal energy, together with the adiabatic heat inside the material created by the mechanical mixing process, makes the mixed materials softer without stirring. As the pin travels forward, the material is pushed to the rear by a distinctive contour on the lead face, which helps to solidify the produced joint. This procedure through the tool in a plasticized tubular metal shaft leads to a severe solid deformation, with the consequence that the base material becomes dynamically recrystallized [6] (see Fig. 1).

FSW offers potential benefits over traditional fusion soldering techniques. Good mechanical characteristics, safety, Easily mechanized for basic milling machinery, typically good weld appearance and minimal thickness, reduced tool consumption, minimum welding area, low environmental effect, overall fusion-to-friction performance, and cost [7]. Some of the downsides include the exit hole on the left when the tool is withdrawn, which demands large down pressures, with a solid clamping to hold the plates together.

The objective of this work is to investigate the mechanical properties such as Hardness and fracture characteristics in the different welding zone. Based on the literature survey, the investigation of the following materials AA7475-T651 and AA2219-O is very rare because of the hardness and melting characteristics. So in this paper, the AA7475-T651 and AA2219-O welded by FSW and its hardness and fraction analysis are evaluated.

Access through your organization

Check access to the full text by signing in through your organization.

Access through **your organization**

Section snippets

Tool design

The tool's design is essential because the right tool may improve both welding quality and fast soldering speed. The materials are desirable to be sufficiently strong, difficult, and stiff at soldering temperatures....

Rotation of tool and traverse speeds

Two device speeds should be considered in friction-stir welding, the speed of tool rotation and the speed of crossing. These two criteria are important and should be carefully set to guarantee that the welding cycle has successfully and efficiently. The connection between the welding ...

Result and graphs

The Fractography is evaluated and given with their dissimilar welding of Al alloys AA7475-T651 and AA2219-O are welded by FSW. The traction failure happens mostly in the stir zone or to the base metal region where Al alloy AA2219-O of low force is located on the forward side of the tractor. The welding zone needs to investigate to quality of the welding and defect identification, the welding zone shown in Fig. 2, Fig. 3.

The extreme enlargement of the SEM images reveals a series of randomly...

Conclusion

Friction stir welding is done successfully on dissimilar aluminum alloys AA7475-T651 and AA2219-O, and their physical properties were tested and analyzed, providing details that welded area contains good grain structure and chemical properties.

1. Hardness test is done on friction stir welded material, and the table shows the different welding zone hardness levels and also which indicate the impact of the welding. Normally the AA2219-O has a low hardness range, but it welds with AA7475-T651, the...

...

CRedit authorship contribution statement

R. Raja: Conceptualization. **A. Parthiban:** Validation. **S. Jeyakumar:** Formal analysis. **B. Radha Krishnan:** Resources....

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper....

[Special issue articles](#) [Recommended articles](#)

References (9)

Abdel-Rahman, M., Kamel, N.A., Lotfy, Y.A., Badawi, E.A. and Abdel-Rahman, M.A., 2008. Defect investigation of...

P. Rombaut *et al.*

Friction welding of steel to ceramic (2011)

P. Prakash *et al.*

A study of process parameters of friction stir welded AA 6061 aluminum alloy

Int. J. Innov. Res. Sci. Eng. Technol. (2013)

A. Vairis

Mathematical modelling of the linear friction welding process

J. Eng. Sci. Technol. Rev. (2012)

There are more references available in the full text version of this article.

Cited by (6)

[Friction stir welding of as-cast and pre-aged Al–Si–Zn–Mg–Fe alloy: Microstructure, mechanical and corrosion properties](#)

2024, Journal of Materials Research and Technology

[Show abstract](#) 

[Magnetic pulse welding of AA6061 and AISI 1020 steel tubes: Numerical and experimental investigation](#)

2023, Journal of Manufacturing Processes

[Show abstract](#) 

[Investigation on the mechanical properties and microstructural analysis of dissimilar friction stir welding of AA5154/AA7150](#)

2024, Journal of Adhesion Science and Technology

[New Characteristics of Welding Materials During Intelligent Manufacturing](#)

2023, Cailiao Daobao/Materials Reports

[Determining the range of process parameters for friction stir welding using steepest ascent approach](#)

2023, Engineering Research Express

[Experimental Studies on Mechanical Behavior of TIG and Friction Stir Welded AA5083 -AA7075 Dissimilar Aluminum Alloys](#)

2023, Advances in Materials Science and Engineering

[View full text](#)

Copyright © 2022 Elsevier Ltd. All rights reserved. Selection and peer-review under responsibility of the scientific committee of the International Conference on Latest Developments in Materials & Manufacturing



All content on this site: Copyright © 2024 Elsevier B.V., its licensors, and contributors. All rights are reserved, including those for text and data mining, AI training, and similar technologies. For all open access content, the Creative Commons licensing terms apply.

